

IT	PART No.	Description	UNET	qty	UNIT PRICE	Total Price
1	Metro C5 E	Metro C5 E-Series Holding/Proofing Cabinet, Full Height, Full Length Clear Door, Universal Wire Slides, 120V, 60Hz, 2000W	EA	4		
2	H-137-UA-12D	HOT CABINT CRES COR STANILSS STEEL, MODEL H137UA12, 120V, 1PH, 1500W	EA	4		
3	TWT-93D-6	True TWT-93D-6-HC 93" 6-Drawer Worktop Refrigerator 30.9 cu ft	EA	4		
4	AM16-BAS-2	Hobart AM16-BAS-2 Standard 17 Inch Opening High Temp Sanitizing Door Style Dishwasher Single Tank 208 to 240 Volts 3 Phase	EA	2		
5	Inomak MIV714	Inomak MIV714 Bain Marie With Glass Structure 4x GN1/1	EA	2		
6	RFI75132	Ice Maker by Isotherm 230V/60Hz Stainless Steel	EA	4		
7	C152 US	Soft Ice Cream Machine C152 US Product Nr: L20108 Model Nr: C152 230 1 60Hz - 1,1kW		2		
8	Model C712	Model C712 – High Capacity Floor Twin Twist Soft Serve Machine		2		
9	HL800-1STD	PLANETARY MIXER Hobart Canada Model No. HL800-1STD Legacy Planetary Mixer, 3.0 HP, 80 quart capacity, four fixed speeds plus stir speed, gear transmission, 50 min SmartTimer, power bowl lift, stainless steel bowl, "B" beater, "ED" dough hook, bowl truck, stainless steel bowl guard, 200-240/50/60/3		1		

10	HL300-1STD	PLANETARY MIXER Hobart Canada Model No. HL300-1STD Legacy Planetary Mixer, 3/4 hp, 200-240/50/60/3, 30 quart capacity, (3) fixed speeds, gear-driven transmission, 15 min. timer, #12 taper attachment hub manual bowl lift, bowl guard, SS Bowl, "B" beater "D" whip&		2		
11	. 6614-2	BONE SAW, ELECTRIC Hobart Canada Model No. 6614-2 Meat Saw, vertical blade, 14" Pulleys, 3500 fpm, 3 Hp motor, direct gear transmission, stainless steel open 20,728.96 10,364.48 frame design, push/pull switch, moveable-lockable carriage tray, two piece stationary rear cutting table adjustable legs (2" movement), hose down capability Voltage 1/60/50/240-200 2-6614 Specification US/Export Configuration, Standard Packaging , no power cord		2		
12	6801-22	MEAT BONE SAW, ELECTRIC Hobart Canada Model No. 6801-22 Meat Saw, vertical blade, 16" Pulleys, 4150 fpm, 3 Hp motor, direct gear transmission, stainless steel open frame design, push/pull switch, moveable-lockable carriage tray, two piece stationary rear cutting table adjustable legs (2" movement), hose down capability Voltage 3/60/240-208 22-6801 Specification, Canada Configuration, Standard Packaging, without Cord & Plug		2		
13	Frame Presses 'SLZ 53"	Laundry Presses "Z" Frame Presses SLZ 53" Laundry Legger		2		
14	-CL64EN BAS+BUILDUP	DISHWASHER, CONVEYOR TYPE Hobart Canada Internal Model No. -CL64EN BAS+BUILDUP Conveyor Dishwasher, (2) tank, (342) racks/hour		2		

		insulated hinged doors, .39 gallon/rack, stainless steel enclosure panels, controls with low temperature & dirty water indicators, NSF Pot & Pan mode, programable de-lime notification, ENERGY @STAR CL64EN-BASELE0AX 208v/60/3- ph, electric heat only CL64EN-BASHT15K Electric tank heat 15kW wash/10kW rinse CL64EN-BASERH30K 30kW electric booster CL64EN-BASDIRVER Verify direction of operation CL64EN-BASHGTSTD Standard height CL64EN-BASFETSTD Standard feet NOTE: For water over 3-grains of hardness, Hobart suggests adding a water softener DTV-CLEN Drain water tempering kit for CLEN models VNTHD/E-ADJ E-series vent hood domestic (adjustable) CLE/TBL-SWITCH Table LMT switch CLE-Series				
15	AM15-2	DISHWASHER, DOOR TYPE Hobart Canada Model No. AM15-2 Dishwasher, door type, hot water/chemical sanitizing 65-58 racks/hour, straight-thru or corner, solid-state controls with digital status, with booster heater, electric tank heat, PRV included, auto-fill, stainless steel tank, frame doors & feet, 208-240/60/3, 5 kW (machine) kW (booster) 5 3/60/240-208 ENERGY STAR SPEC-KIT Single point electrical connect AM15 kit (field installation required) (3 phase (booster machines only DWT-AM15 Drain water tempering kit		2		
16		MICROWAVE, STAINLESS STEEL V, 60HZ, 1HP208		5		
17		MILNOR 60 LB FRONT LOAD WASHER EXTRACTOR 30022 C4E		2		
18		DRYER CLOTHES CONTINENTAL, GIRBAN INC CG LBS 50 60-50		2		

