

systems from small mechanical thermometers that hang or stick inside refrigerated units to more sophisticated panel temperatures to stay compliant and prevent food spoilage.



535

Cooler
Thermometer

-20° to 120°F
(-30° to 50°C)

±5°F (±2°C)

Plastic

2"
(51 mm)

Plastic

0.5 oz (14 g)

-

1 Year



2560

Digital
Thermometer

-22° to 122°F
(-30° to 50°C)

±1°F (±0.5°C)

Antimicrobial
Plastic

3.562 x 1.25"
x 3.5"
(90 mm x 32 mm
x 89 mm)

Food Grade
Polycarbonate

1.5 oz (43 g)

CE NSF RoHS

Lifetime



PM180

Dual-Cool

-25° to 180°F
(-32° to 82°C)

±2°F (±1°C)

Plastic

-

-

5 oz (142 g)

CE RoHS

1 year



RECALL SEPARATE MIN / MAX
TEMPERATURES FOR EACH PROBE!

PM180-01

- PM180 Panel Thermometer
- 2013 Air Probe
- 2113 Solid Simulator Probe

PM180-02

- PM180 Panel Thermometer
- (2) 2013 Air Probe

PM180-03

- PM180 Panel Thermometer
- (2) 2113 Solid Simulator Probe

Dual-Cool (PM180)
Cooper-Atkins' first dual temperature panel thermometer with interchangeable probes, Min/Max alarm settings and Hi/Lo temperature recall. Equipped with user-adjustable settings, it can simultaneously measure temperatures within two separate storage environments.