## **GLASS DOOR BACK BAR COOLER**

### EBB – Series Model : EBB48G





Operating temperature range is 32°F ~ 42°F





#### **Cabinet Construction**

Heavy duty stainless steel countertop, textured and laminated black vinyl exterior. Galvanized steel interior wall, and high quality stainless steel floor. 1 3/4" thick high density foamed-in-place polyurethane insulation. Built-in caster thread receptacles.

#### **Refrigeration System**

- Side mounted condensing unit
- Oversized condenser and evaporator coils quickly achieve and maintain desired temperature
- $\cdot$  Forced-air cooling with oversized evaporator fan motors providing balanced airflow throughout cabinet to ensure faster temperature drop
- Removable side panel and slide-out condensing unit for convenient repair and maintenance
- Environmentally friendly CFC free R-134A refrigerant
- · Air defrost controlled by electrical timer
- · Copper tube and aluminum fin evaporator with anti-corrosive coating
- · Energy efficient condensate drain pan assembly heated by high side copper tube
- · Pre-wired and ready to plug, 115V/60Hz/1Ph, NEMA 5-15P

#### Doors

- · Black PVC door frames
- · Low emissivity double pane glass system reflects UV rays and improves
- · insulation for maximized energy efficiency
- · One piece snap-in magnetic door gaskets for easy replacement
- · Heavy duty die cast door handles
- · Door locks

#### Lighting

Shielded vertical LED interior lighting with on/off switch for energy saving, less
heat generation and enhanced illumination (available from 2015 models)

#### Shelving

- · Two epoxy coated wire shelves per section
- Stainless steel pilasters and shelf clips

#### **Temperature Control**

- · Factory preset temperature, 35°F
- Temperature setting range from 32°F to 42°F
- · Easy to set analog thermostat

#### Option

· 2 1/2" and 4" diameter casters (3 1/2" and 5" overall height)

Model	# of	Capacity <sup>►</sup>	HP	Refrigerant	# of	Capacity 20 oz.	Power	Amps	Crated	Exte	erior Dimensi	ons
mouor	Doors	(Cu. Ft.)		nonigorani	Shelves	Cans / Bottles	(V-Hz-Ph)	7 mpo	Weight	L	D	Н
EBB48G	2	14.4	1/4+	R-134A	4	490 / 258	115-60-1	4.20	289 lbs (131 kg)	49'' (1246 mm)	27'' (685 mm)	37 1/4'' (946 mm)

† : Depth does not include protruding door handles.

Specifications subject to change without notice.

Product dimensions are for general purposes and not absolute value. Product capacity(r) is calculated based on standard industry figures. Slight variations may exist. If dimensions and capacity are critical, please contact Everest Refrigeration.


# **GLASS DOOR BACK BAR COOLER**


### EBB – Series Model : EBB48G




Net capacit	v cu. ft.	14.4 (407.7 cu l)		
	Length Overall in.	49" (1246)		
Exterior	Depth Overall in. <sup>†</sup>	27" (685)		
(mm)	Height Overall in.	37 1/4" (946)		
Interior	Length Overall in.	34 1/4" (869)		
(mm)	Depth Overall in.	23 1/4" (590)		
	Height Overall in.	31 1/4" (795)		
Crated Wei	ght	289 lbs (131 kg)		
# of Doors		2		
# of Shelve	S	4		
Capacity 20	loz. (Cans / Bottles)	490 / 258		
Shelf Size L (mm)	ength x Depth in.	16 1/2" x 20 7/8" (420 X 530) 18 1/2" x 20 7/8" (470 x 530)		
ELECTRI	CAL DATA			
Voltage (V-I	Hz-Ph)	115-60-1		
Full load an	nperes	4.20		
Feed wires	with Ground	3		
Cord Lengt	ı ft.	9		
REFRIGE	RATION DATA			
Refrigerant		R-134A		
Compresso	r H.P.	1/4+ HP		
btu/hr <sup>a</sup> (f		2075 (523)		

### Dimensions inches (mm)







341/4 (869)

3 (75)

371/4 (946)

Specifications subject to change without notice.

+ : Depth does not include protruding door handles.
a : Based on evaporating temperature of 23°F(-5°C) & Condensing temperature of 131°F(55°C).