Specifications

1) Stainless Steel Construction:

Entire cabinet constructed of heavygauge, polished, sanitary stainless steel; precision welded to withstand years of use and abuse.

9) Patented Legs: Our patented leg design (Patent No. 7,543,459) provides a wide footing for increased stability and less vibration. The flow through leg footings allows water to flow freely to drain out of the drip pan.

8) Patented Ratchet Drive:

Our patented ratchet cam drive system (Patent No. 7,536,871) eliminates all slippage and smoothly advances the block ice for perfectly controlled ice shaving.

7) Polycarbonate Door: Door and frame are made of "bullet proof* polycarbonate which is impervious to oxidation and corrosion due to water and mineral deposits.

2) Waterproof Motor Switch:

Commercial grade, military spec, sealed waterproof lever switch protects against moisture and water from wet hands.



6) Stainless Steel Blades: Proper composition of stainless steel and carbon steels hardened to 53 on the Rockwell scale. Sanitary, resists corrosion and holds an edge longer than

regular blades.

3) Tri-cutter Head: Machined aluminum cutter head designed to hold the three stainless blades on the same cutting plane to quickly shave ice into fluffy anow.

4) Belt Guard: Stainless steel belt guard designed to aesthetically enhance the appearance of the machine while functionally protecting the operator from the moving belt and pulleys.

Stainless Steel Bearings &

Engineered Pulley: Rust-proof zinc pulley and stainless steel sealed roller bearings engineered to mate and provide smooth, maintenance free operation. This combination, unique to the SnoWizard® alone, allows for true spinning of the cutter mechanism thus achieving the finest anow possible.

28" Height:

Depth:

Width: 33"; (with ratchet bar extended: 52")

Drip Pan: 35" W x 25" D x 5" H

36" W x 26" D (for extra work/materials area:

counter size: 66" W x 26" D)

1725RPM, 115V, 1/2 HP, CCW, 115 Volt, Motor:

60hz, Single phase, 8.8 Amps.

Options: 12 Volt DC or 220 Volt AC.

Belt: FHP V-Belt, 38" outside length.

LG pulley: OD: 8' 5/8 bore

SM pulley: OD: 2.5" 5/8 bore.

Lubricant: USDA waterproof Foodservice Grease. 52" with retchet ber 27%

Cutting blades: hardened, high carbon

stainless steel, anti-

corrosive.

Construction: Unibody welded.

ice size:

Recommended 5.5" square x 15" long (12.5

Lbs.)

Max ice size: 6"x6"x15"

long (15

Lbs.)

Actual Weight: 100 Lbs.

Shipping Weight: 110 Lbs.



The SnoWizard SnoBall Machine® is built and tested to conform to National Sanitation Foundation (NSF) and Underwriter Laboratories (UL) standards and has earned the ETL seal of approval which is recognized in all 50 States and Canada.



