

TRUE FOOD SERVICE EQUIPMENT, INC.

2001 East Terra Lane • O'Fallon, Missouri 63366-4434 • (636)240-2400 Fax (636)272-2408 • Toll Free (800)325-6152 • Intl Fax# (001)636-272-7546 Parts Dept. (800)424-TRUE • Parts Dept. Fax# (636)272-9471 • www.truemfg.com Project Name: ____

Item #: _____

Location: _____

Model #:

Qty:	SIS #
· · ·	

AIA #

Model: GDM-23W-HC-LD

Glass Door Wine Merchandiser:

Swing Door Refrigerator with Hydrocarbon Refrigerant & LED Lighting



GDM-23W-HC-LD

- The world's #1 manufacturer of glass door merchandisers.
- Factory engineered, self-contained, capillary tube system using environmentally friendly R290 hydro carbon refrigerant that has zero (0) ozone depletion potential (ODP), & three (3) global warming potential (GWP).
- High capacity, factory balanced refrigeration system that maintains cabinet temperatures of 33°F to 38°F (.5°C to 3.3°C) for the best in food preservation.
- Exterior non-peel or chip black laminated vinyl; durable and permanent.
- Interior attractive, NSF approved, black aluminum interior sides and top liner with stainless steel floor. Mirrored back wall.
- Self closing door. Positive seal, torsion type closure system. Door lock standard.
- "Low-E", double pane thermal insulated glass door assembly with extruded aluminum frame. The latest in energy efficient technology.
- LED interior lighting provides more even lighting throughout the cabinet. Safety shielded.
- Entire cabinet structure is foamed-inplace using a high density, polyurethane insulation that has zero ozone depletion potential (ODP) and zero global warming potential (GWP).
- Four (4) adjustable wine racks and one (1) adjustable, heavy duty, black PVC coated wire shelf.

Bottom mounted units feature

- "No stoop" lower shelf to maximize product visibility.
- Storage on top of cabinet.
- Easily accessible condenser coil for cleaning.

ROUGH-IN DATA

 $\label{eq:specifications subject to change without notice. Chart dimensions rounded up to the nearest <math display="inline">\%$ " (millimeters rounded up to next whole number).

		Shelves			oinet Dimensions (inches) (mm)					NEMA	Cord Length (total ft.)	Crated Weight (lbs.)
Model	Doors	Wire	Wine	W	D†	Н	HP	Voltage	Amps	Config.	(total m)	(kg)
GDM-23W-HC-LD	1	1	4	27	297⁄8	785⁄8	1⁄3	115/60/1	5.4	5-15P	9	305
				686	759	1998	N/A		N/A		2.74	139

† Depth does not include 11/8" (29 mm) for door handle.

	APPROVALS:	AVAILABLE AT:
10/15 Printed in U.S.A.		

Model:

GDM-23W-HC-LD

Glass Door Wine Merchandiser: Swing Door Refrigerator with Hydrocarbon Refrigerant & LED Lighting



STANDARD FEATURES

DESIGN

• True's commitment to using the highest guality materials and oversized refrigeration systems provides the user with colder product temperatures, and lower utility costs in an attractive merchandiser that brilliantly displays wine and alcohol products.

REFRIGERATION SYSTEM

- Factory engineered, self-contained, capillary tube system using environmentally friendly R290 hydrocarbon refrigerant that has zero (0) ozone depletion potential (ODP), & three (3) global warming potential (GWP).
- High capacity, factory balanced refrigeration system that maintains cabinet temperatures of 33°F to 38°F (.5°C to 3.3°C) for the best in food preservation.
- State of the art, electronically commutated evaporator and condenser fan motors. ECM motors operate at higher peak efficiencies and move a more consistent volume of air which produces less heat, reduces energy consumption and provides greater motor reliability.
- Bottom mounted condensing unit positioned for easy maintenance. "No stoop" lower shelf maximizes visibility by raising merchandised product to higher level.

CABINET CONSTRUCTION

- Exterior non-peel or chip black laminated vinyl; durable and permanent.
- Interior attractive, NSF approved, black aluminum sides and top liner with stainless steel floor. Mirrored interior back.

- · Insulation entire cabinet structure is foamedin-place using a high density, polyurethane insulation that has zero ozone depletion potential (ODP) and zero global warming potential (GWP).
- Welded, heavy duty steel frame rail, black powder coated for corrosion protection.
- Frame rail fitted with leg levelers.
- Illuminated exterior sign panel. Variety of sign options available.

DOOR

- "Low-E", double pane thermal insulated glass door assembly with extruded aluminum frame. The latest in energy efficient technology. Door lock standard.
- Door fitted with 12" (305 mm) long extruded handle.
- Self closing door. Positive seal, torsion type closure system.
- Magnetic door gasket of one piece construction, removable without tools for ease of cleaning.

SHELVING

- Four (4) adjustable wine racks 22 % "L x 21 % "D (574 mm x 537 mm) and one (1) adjustable, heavy duty, black PVC coated wire shelf 22 %6"L x 23 ¼ "D (574 mm x 591 mm). Four (4) chrome plated shelf clips included per rack and shelf.
- Shelf support pilasters made of same material as cabinet interior; shelves are adjustable on 1/2" (13 mm) increments.

LIGHTING

 LED interior lighting provides more even lighting throughout the cabinet. Safety shielded.

MODEL FEATURES

- Evaporator is epoxy coated to eliminate the potential of corrosion.
- See our website www.truemfg.com for latest color and sign offerings.
- Convenient clean-out drain built in cabinet floor.

ELECTRICAL

• Unit completely pre-wired at factory and ready for final connection to a 115/60/1 phase, 15 amp dedicated outlet. Cord and plug set included.





OPTIONAL FEATURES/ACCESSORIES

Upcharge and lead times may apply. U White exterior.

- □ 6" (153 mm) standard legs.
- □ 6" (153 mm) seismic/flanged legs.
- □ 2½" (64 mm) diameter castors.
- Red wine thermostat.
- U White wine thermostat.
- Chocolate thermostat.
- Sliding wine racks.
- Additional black wine racks.
- Additional black wire shelves.
- U White wire shelves.
- □ TrueTracIII gravity feed organizers.
- □ TrueTrac4 gravity feed organizers.
- □ 1¼" (32 mm) pricing strips.

PLAN VIEW





PLAN VIEW

Three year warranty on all parts	METRIC DIMENSIONS ROUNDED UP TO THE .							
and labor and an additional 2 year warranty on compressor.	NEAREST WHOLE MILLIMETER		Model	Elevation	Right	Plan	3D	Back
(U.S.A. only)	SPECIFICATIONS SUBJECT TO CHANGE	KCL	GDM-23W-HC-LD	TFAZ03E	TFAY03S	TFAZ03P	TFAZ033	
RESIDENTIAL APPLICATIONS: TRUE assumes no liability for parts abor coverage for component failure or other damages resulting rom installation in non-commercial or residential applications.				1	1	1	1	

TRUE FOOD SERVICE EQUIPMENT

2001 East Terra Lane • O'Fallon, Missouri 63366-4434 • (636)240-2400 • Fax (636)272-2408 • Toll Free (800)325-6152 • Intl. Fax# (001)636-272-7546 • www.truemfg.com